

SAFETY DATA SHEET (SDS) DP-REPAIR-F

1. IDENTIFICATION

Product Name: Acrylic resin DP-Repair-F

Other Name or Code: 1071100, 1071200, 1071300, 1071101, 1071201, 1071301

1071102, 1071202, 1071302, 1071103, 1071203, 1071303 1071105, 1071204, 1071304, 1071107, 1071207, 1071307

1071116, 1071216, 1071316

Use: Repair systems for dentures

Supplier Name: DenPlus Inc.

Address: 333-M Chemin du Tremblay

Boucherville, QC, Canada, J4B 7M1

Phone Number for Information: 450.641.1330 Emergency Phone Number: 613.996.6666 Anti-Poison Center of Quebec 1.800.463.5060

2. HAZARDS IDENTIFICATION

2.1 Classification

Combustible dust - Category 1

2.2 Label elements

Signal word: Warning

Hazard statement: May form combustible dust concentrations in air

3. INFORMATION ON INGREDIENTS

Polymer beads based on methyl methacrylate and 2-ethylhexyl acrylate containing residual peroxide.

Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below.

Hazardous ingredients	CAS	Concentration
		range
		(by weight)
Dibenzoyl peroxide	000094-36-0	1-2 %
Methyl methacrylate	000080-62-6	<1 %
2-Ethylhexyl acrylate	000103-11-7	<1 %

DenPlus IncDP-Repair-F ResinDate: May 5, 2023Page 1 of 6

4. FIRST-AID MEASURES

4.1 Description of first aid measures

Inhalation IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a

poison center or doctor if you feel unwell.

Skin Contact IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs, get medical

attention.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. Get medical attention if ill effects occur.

Ingestion IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Obtain medical attention if

ill effects occur.

4.2 Most important symptoms and effects, both acute and delayed

Not applicable.

4.3 Indication of any immediate medical attention and special treatment needed

None necessary.

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

In case of fire, use water spray, carbon dioxide (CO₂), spray foam, dry powder. Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Combustible but not readily ignited. Combustion or thermal decomposition will evolve toxic, irritant or flammable vapors. This product can form flammable dust clouds at elevated temperatures. The minimum ignition temperature of a dust cloud of a similar polymer has been measured at approximately 480 °C.

5.3 Advice for firefighters

A self-contained breathing apparatus and suitable protective clothing should be worm in fire conditions.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Caution – spillage may be slippery.

6.2 Environmental precautions

Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

Collect in containers for disposal using approved dust respirator.

6.4 Reference to other sections

See sections: 8 and 13

DenPlus IncDP-Repair-F ResinDate: May 5, 2023Page 2 of 6

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Do not eat, drink or smoke at the work place.

Product as supplied: Avoid contact with eyes. Avoid prolonged skin contact. Unlikely to represent a dust hazard under normal handling conditions.

Dental resins are usually processed in conjunction with reactive monomers and this may require the use of a higher level of protection than the necessary for the polymer itself.

7.2 Conditions for safe storage, including any incompatibilities

Acrylic polymers are supplied in either bags or bulk containers. Keep containers in a clean, cool and dry area away from heat sources. Natural ventilation is adequate.

Storage temperature (°C): Ambient.

Incompatible materials: Polymer contains residual benzoyl peroxide. This may react with oxidizing

agents, reducing agents, acids, bases and amines leading to

decomposition.

7.3 Specific end use(s)

Production of dentures.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 Control parameters

Substance	CAS No.	OSHA PEL	ACGIH	ACGIH	Company	Company
		TWA	TWA	STEL	Std.	Std.
					TWA	STEL
Dibenzoyl peroxyde	000094-36-0	5 mg/m ³	5 mg/m ³ (A4)			
Particulates (Total dust)		15 mg/m ³	10 mg/m ³			
Dust (Respirable dust)		5 mg/m ³	3 mg/m ³			
The following values						
apply to substances						
which may be evolved						
during thermal						
processing						
Methyl methacrylate	000080-62-6	100 ppm	50 ppm	100 ppm	50 ppm	100 ppm
		410 mg/m ³	(205 mg/m^3)	(205 mg/m^3)		
				SEN;A4		
2-Ethylhexyl acrylate	000103-11-7				5 ppm	
					(41 mg/m^3)	
					(Skin)	

DenPlus IncDP-Repair-F ResinDate: May 5, 2023Page 3 of 6

8.2 Exposure controls

Appropriate engineering controls

Do not eat, drink or smoke at the work place. Provide adequate ventilation, including appropriate local extraction, to ensure that the occupational exposure limit is not exceeded. Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required. The following information is given as general guidance.

Individual protection measures

Eye/face protection Wear eye/face protection. Safety spectacles/goggles/full face shield. Skin protection Not normally required, however use of gloves is recommended.

Suitability of gloves should be confirmed with glove manufacturer.

Respiratory protection A suitable dust mask or dust respirator with filter type P3 or FFP3 may be

appropriate. In the unlikely event of formation of particularly high levels of

dust a self contained breathing apparatus may be appropriate.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance White or colored powder Odor Typically methacrylate

pH (Value)

Melting Range (°C)

Boiling Point (°C)

Not applicable

Not applicable

Flash Point (°C) ~ 390

Flammability (solid, gas)

Flammable Limits

Vapor pressure (Pascal)

Vapor Density (Air=1)

Solubility (Water)

Solubility (Other)

Partition Coefficient (n-Octanol/water)

Not applicable

Not applicable

Not applicable

Auto Ignition Temperature (°C) ~ 465

Viscosity (mPa. s) Not available

Explosive properties Weakly to moderately explosive

Oxidizing properties Not applicable Density (g/ml) 1.1 - 1.18

10. STABILITY AND REACTIVITY

10.1 Reactivity

Non-reactive material.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

None known.

10.4 Conditions to avoid

Avoid dust generation.

10.5 Incompatible materials

Polymer contains residual benzoyl peroxide. This may react with oxidizing agents, reducing agents, acids, bases and amine leading to decomposition.

10.6 Hazardous decomposition products

Methyl methacrylate, n-butyl methacrylate, dibenzoyl peroxide, carbon dioxide, carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Ingestion Low oral toxicity.

Inhalation Unlikely to be hazardous by inhalation. High concentrations of

dust may be irritant to the respiratory tract. High concentrations of vapour from hot operations may be harmful, cause irritation of

the respiratory tract and slight narcotic effects.

Skin contact It is not a skin sensitizer. Eye contact Dust may cause irritation.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

This product is predicted to have low toxicity to aquatic organisms.

12.2 Persistence and degradability

This product is non-biodegradable in soil. There is no evidence of degradation in soil and water.

12.3 Bioaccumulative potential

The product has low potential for bioaccumulation.

12.4 Mobility in soil

The product is predicted to have low mobility in soil.

12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

12.6 Other adverse effects

None known.

13. DISPOSAL CONSIDERATIONS

The waste is considered to be non hazardous. Clean scrap may be reprocessed. Dispose in accordance with local regulations.

13.1 Waste treatment methods

May be disposed of by landfill in accordance with local regulations.

14. TRANSPORTATION CONSIDERATIONS

Not Classified as Dangerous for Transport.

14.1 UN number Not applicable.

14.2 UN Proper Shipping Name Not applicable.

14.3 Transport hazard class(es) Not applicable.

14.4 Packing group Not applicable.

14.5 Environmental hazards Not applicable.

14.6 Special precautions for user Not applicable.

14.7 Transport in bulk according to Annex II

of MARPOL and the IBC Code Not applicable.

15. REGULATORY INFORMATION

WHMIS 2015

Canadian Hazardous Products Regulations (SORS2015-17)
Canadian Hazardous Products Act (R.S.C., 1985, c. H-3)
Hazardous Products Information Regulation (Quebec S-2.1, r. 8.1)

16. OTHER INFORMATION

The following sections contain revisions or new statements: 3, 8, 11, 16

Date of revision: May 5, 2023

The information in this SDS was obtained from sources, which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. We do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.