



SAFETY DATA SHEET (SDS)

TRAY-F LIQUID

1. IDENTIFICATION

Product Name: Acrylic Liquid Tray-F for Premium Tray resins
Other Name or Code: 1122100 or 1122200
Use: Dental custom trays.
Supplier Name: DenPlus Inc.
Address: 333-M Chemin du Tremblay
Boucherville, QC, Canada, J4B 7M1
Phone Number for Information: 450.641.1330
Emergency Phone Number: 613.996.6666
Anti-Poison Center of Quebec 1.800.463.5060

2. HAZARDS IDENTIFICATION

2.1 Classification

Flammable liquid - Category 2	H225	Highly flammable liquid and vapor
Acute toxicity (oral) – Category 4	H302	Harmful if swallowed
Aspiration hazard – Category 1	H304	May be fatal if swallowed and enters airways
Skin corrosion/irritation - Category 2	H315	Causes skin irritation
Skin sensitization – Category 1	H317	May cause an allergic skin reaction
Serious eye damage/eye irritation - Category 2B	H320	Cause eye irritation
Specific target organ toxicity (STOT) - single exposure - Category 2	H371	May cause damage to organs

2.2 Label elements



Signal word: Danger

Hazard statements: H225 Highly flammable liquid and vapor
H302 Harmful if swallowed
H304 May be fatal if swallowed and enters airways
H315 Causes skin irritation
H317 May cause an allergic skin reaction
H320 Cause eye irritation
H371 May cause damage to organs

Precautionary statements:	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.
	P261	Avoid breathing vapors.
	P280	wear protective gloves/protective clothing/eye protection/face protection.
	P301+P310	IF SWALLOWED: Immediately call a doctor.
	P302+P352	IF ON SKIN: Wash with plenty of water.
	P304+P340	IF INHALED: remove person to fresh air and keep comfortable for breathing.
	P501	Dispose of contents/container to hazardous waste in accordance with local, state or national legislation. Incinerate under approved controlled conditions, using incinerators suitable for the disposal of flammable organics.

3. INFORMATION ON INGREDIENTS

Hazardous ingredients	CAS	Concentration range
Methyl Methacrylate Monomer Inhibited	80-62-6	80 to 100 %
Methanol	67-56-1	5 to 10 %
N,N-Dimethyl-p-toluidine	99-97-8	0.1 to 1 %

4. FIRST-AID MEASURES

4.1 Description of first aid measures

Information	Methyl methacrylate is absorbed into the body by inhalation, swallowing and through the skin.
Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.
Skin Contact	IF ON SKIN (or hair): Wash with plenty of water. If skin irritation or rash occurs, get medical attention. Take off contaminated clothing.
Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain immediate medical attention.
Ingestion	IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Obtain immediate medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Causes skin irritation. May cause respiratory irritation. May cause an allergic skin reaction. May cause damage to organs. May be fatal if swallowed and enters airways. High atmospheric concentrations may lead to irritation of the respiratory tract and anaesthetic effects. Repeated and/or prolonged contact may cause dermatitis.

4.3 Indication of any immediate medical attention and special treatment needed

Methanol - Symptomatic treatment and supportive therapy as indicated. Following ingestion onset of symptoms may be delayed by 12-24 hours and admission to hospital should be the first priority even if symptoms are absent. Gastric lavage or emesis should be performed as soon as possible to minimize absorption, and is recommended within 4 hours of ingestion. Ethanol may be given intravenously as an antidote to prevent build up of toxic metabolites and increase extra hepatic elimination of Methanol. Visual disturbances and metabolic acidosis may occur and dialysis, preferably hemodialysis, may be employed to treat these complications and to remove Methanol and its metabolites from the blood. Intravenous folic acid may also assist in reducing the toxic effects of Methanol metabolites.

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

In case of fire, use water spray, carbon dioxide (CO₂), spray foam, dry powder. Keep containers cool by spraying water if exposed to fire. Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Highly flammable liquid and vapor. May polymerize on heating. Sealed containers may rupture explosively if hot.

5.3 Advice for firefighters

A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Eliminate sources of ignition. Wear protective gloves and eye/face protection. Avoid breathing vapors. See section 8.

6.2 Environmental precautions

Avoid release to the environment. Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Collect spillage. Adsorb spillages onto sand, earth or any suitable adsorbent material. Do not adsorb onto sawdust or other combustible materials. Transfer to a lidded container for disposal or recovery. Use only non-sparking tools.

6.4 Reference to other sections

See sections: 8 and 13

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Do not eat, drink or smoke at the work place. Wash thoroughly after handling. Avoid breathing vapors. Use only outdoors or in a well-ventilated area. The vapor is heavier than air; beware of pits and confined spaces. Ground container and receiving equipment. Use explosion proof electrical equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight.

Storage temperature (°C): Preferably not exceeding 25°C.

Incompatible materials: Polymerization catalysts, such as peroxy or azo compounds, strong acids, alkalis and oxidizing agents. Oxides and salts of transition metals. Organic Nitrogen containing compounds. Cyclohexanone/Cyclohexenol tautomer.

7.3 Specific end use(s)

Manufacture of custom dental trays.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 Control parameters:

Substance	LTEL	LTEL	STEL	STEL
Methyl Methacrylate	205 mg/m ³	50 ppm	416 mg/m ³	100 ppm
Methanol	265 mg/m ³	200 ppm	333 mg/m ³	250 ppm

LTEL: Long-term exposure limit

STEL: Short-term exposure limit

8.2 Exposure controls

Appropriate engineering controls

Do not eat, drink or smoke at the work place. Provide adequate ventilation, including appropriate local extraction, to ensure that the occupational exposure limit is not exceeded. Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required. The following information is given as general guidance.

Eye/face protection Wear eye/face protection. Safety spectacles/goggles/full face shield.

<p>Skin protection</p>	<p>Wear suitable gloves. For splash protection: Butyl; EN 374. For immersion protection: Butyl; 0.7 mm or greater; EN 374. Suitability of gloves should be confirmed with glove manufacturer. Change gloves, if contamination occurs or duration of activity exceeds breakthrough time. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.</p>
<p>Respiratory protection</p>	<p>Wear suitable respiratory protective equipment if exposure to levels above the occupational exposure limit is likely. A dust mask is not acceptable. A suitable mask with filter type A (EN141 or EN405) may be appropriate. In the event of formation of particularly high levels of vapor a self contained breathing apparatus may be appropriate.</p>

Environmental exposure controls

Ensure proper process control to ensure releases to air are within local permits. Monitor and regularly maintain ventilation equipment to ensure performance. Do not empty into drains. Contain and collect spillages for incineration. Fully polymerize before landfill. Only dispose of polymerized material with household waste.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear liquid
Odor	Characteristic strong and acrid
pH (Value)	Not applicable
Boiling Point (°C)	100.5
Flash Point (°C)	10 [Closed cup]
Flammability (solid, gas)	Not applicable
Flammable Limits (Lower) (%v/v)	2.1
Flammable Limits (Upper) (%v/v)	12.5
Flammable Limits	Methyl methacrylate
Vapor pressure (Pascal)	3600 at 20°C
Vapor Density (Air=1)	3.5
Solubility (Water)	Slightly soluble 1.6% at 20°C
Solubility (Other)	Miscible with most organic solvents
Partition Coefficient (n-Octanol/water)	1.38
Auto Ignition Temperature (°C)	421
Viscosity (mPa. s)	Not available
Explosive properties	Not applicable
Oxidizing properties	Not applicable
Density (g/ml)	0.949 at 15.5°C

10. STABILITY AND REACTIVITY

10.1 Reactivity

Will exothermically polymerize in the presence of initiators.

10.2 Chemical stability

Stable in the presence of inhibitor.

10.3 Possibility of hazardous reactions

Susceptible to polymerization initiated by prolonged storage or the presence of catalyst.

10.4 Conditions to avoid

Heat and direct sunlight.

10.5 Incompatible materials

Polymerization catalysts, such as peroxy or azo compounds, strong acids, alkalis and oxidizing agents. Oxides and salts of transition metals. Organic Nitrogen containing compounds. Cyclohexanone/Cyclohexenol tautomer.

10.6 Hazardous decomposition products

Does not decompose up to auto-ignition temperature.

11. TOXICOLOGICAL INFORMATION

The following information is based on the principal component: methyl methacrylate.

Acute toxicity

Ingestion

Harmful if swallowed.

Ingestion may cause irritation of the gastrointestinal tract.

May cause damage to organs.

Inhalation

May cause drowsiness and dizziness.

Skin corrosion/irritation

Causes skin irritation. Repeated and/or prolonged contact may cause dermatitis.

Serious eye damage/irritation

High vapor concentration will cause irritation.

Sensitization

Methyl methacrylate , Ethylene glycol dimethacrylate : May cause an allergic skin reaction.

Germ cell mutagenicity

Salmonella typhimurium (TA1535, 1537, 97, 98, 100) negative (OECD 471)

Carcinogenicity

No evidence of carcinogenicity. (OECD 451)

Reproductive toxicity

NOAEC (mouse) = 9000 ppm

NOAEC (rat) > 2028 ppm

STOT - single exposure

May cause respiratory irritation.

STOT - repeated exposure

None.

Aspiration hazard

Not an aspiration hazard.

Chronic exposure

Methyl methacrylate: Repeated exposure to high levels produces adverse effects on the heart, lungs, liver and kidneys. Repeated exposure of animals by inhalation to levels at or above the occupational exposure level produces adverse effects on the nasal epithelium (levels of 100 and 400 ppm). There is no reason to believe that methyl methacrylate represents a carcinogenic or mutagenic hazard to man based upon evidence from well conducted animal studies, relevant mutagenicity studies and adequate epidemiology studies in relevant cohorts. Recent

studies in animals have shown that high exposures do not produce embryo or foeto toxic nor teratogenic effects in the presence of maternal toxicity.

Methanol : Repeated exposure to levels well above the occupational exposure limit may produce systemic effects and visual disturbances which may lead to permanent blindness. Studies in animals have shown that repeated exposures do not produce carcinogenic effects. Studies in animals have shown that high exposures produce embryo/foeto toxic effects in the presence of maternal toxicity. None of these effects are likely to occur in humans, provided exposure is maintained at or below the occupational exposure limit.

NOEL (oral) (rat) (104 weeks) >2000 ppm

NOAEC (inhalation) (rat) (104 weeks) 100 ppm (OECD 453)

NOAEC (inhalation) (mouse) (14 weeks) 1000 ppm (OECD 412)

12. ECOLOGICAL INFORMATION

The following information is based on the principal component: methyl methacrylate.

12.1 Toxicity

Low toxicity to fish.

LC50 (fish) (typically) >100 mg/l

LC50 (fathead minnow) (96 hour) (static) 130 mg/l

Harmful to aquatic invertebrates.

EC50 (Daphnia magna) (48 hour) 69 mg/l

Low toxicity to algae.

EC50 (Selenastrum capricornutum) (96 hour) 170 mg/l

NOEC (zebra fish) (35 days) (flow through) 8.4 mg/l

12.2 Persistence and degradability

Readily biodegradable.

Chemical Oxygen Demand (COD): 88% (28 days)

Inherent Biodegradation:

Dissolved Organic Carbon Removal (DOC removal): >95% (28 days)

12.3 Bioaccumulative potential

The product has low potential for bioaccumulation.

12.4 Mobility in soil

The product is predicted to have high mobility in soil.

12.5 Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

12.6 Other adverse effects

None known.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Dispose of contents/container to hazardous waste in accordance with local, state or national legislation. Incinerate under approved controlled conditions, using incinerators suitable for the disposal of flammable organics. The packaging should be disposed of with due care, ensuring that the package is completely emptied. In some cases the packaging itself may be regarded as a waste requiring special treatment. If in any doubt please seek specialist advice from a competent authority.

14. TRANSPORTATION CONSIDERATIONS

14.1 UN number

1247

14.2 UN Proper Shipping Name

METHYL METHACRYLATE MONOMER, STABILIZED, MIXTURE

14.3 Transport hazard class(es)

Class	3
IMDG Class	3
IMDG EMS	F-E, S-E
IATA	3
ADR Classification Code	F1
ADR HIN	33
ADR Transport Category	2
Tunnel Restriction Code	D/E
RID	3
ADN	3

14.4 Packing group

II

14.5 Environmental hazards

Environmentally hazardous substance	No.
Marine Pollutant	Not classified as a Marine Pollutant.

14.6 Special precautions for user

No special requirements.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable.

15. REGULATORY INFORMATION

WHMIS 2015

Canadian Hazardous Products Regulations (SORS2015-17)

Canadian Hazardous Products Act (R.S.C., 1985, c. H-3)

Hazardous Products Information Regulation (Quebec S-2.1, r. 8.1)

16. OTHER INFORMATION

Date of revision : July 6, 2021

The information in this SDS was obtained from sources, which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or method of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.